

High Speed Colour Duplex Scanner

# *fi*-6125LA



60 images per minute scanning speed  
@ 200 dpi B&W or greyscale

Auto colour detection, blank page deletion,  
auto cropping, and auto de-skew

50 page automatic document feeder

Ultrasonic multi-feed detection


Quiet operation

1 year exchange warranty



**FUJITSU**

# fi-6125LA



## The best cost performer in its class

The fi-6125LA's ability to scan up to 30 ppm or 60 ipm in monochrome / greyscale (Letter, 200 dpi) makes it the top cost performer in its class. Its ability to continuously scan 50 page mixed batch documents containing paper of different weight, quality and sizes enables the fi-6125LA to efficiently digitize large volumes of paper documents. The fi-6125LA is also able to scan up to 3 non-embossed plastic cards or 1 embossed plastic card (up to 1.4 mm thick) at a time.

## Loaded with "intelligent" functions for efficient operation

The fi-6125LA is loaded with high-end fi-Series functions that enable it to efficiently scan mixed batch documents containing paper of different weights, quality and size.

### • Ultra-sonic multi-feed function

Ultra-sonic double feed detection is the most advanced method for detecting double feeds. It works reliably even when scanning pages of different sizes, thicknesses and colours.

### • "Auto-colour recognition", "Auto-size recognition" and "Auto-deskew functionality"

This functionality enables the fi-6125LA to automatically recognize the size of scanned documents, correct skewed images and automatically differentiate colour images from black and white ones.

## Comes bundled with the "automatic job separation" function armed ScandAll PRO image capture software

The fi-6125LA's bundled barcode and patchcode reading functionality enables it to simultaneously scan and automatically separate different jobs with its automatic job separation function. The result is improved digitizing efficiency.

## Imprinter supportability

Use of the fi-6125LA's optional imprinter (fi-614PR) enables users to print dates and other information on the back of the original document, thus easing the search for original documents at a later date.



fi-6125LA with imprinter option.

## TECHNICAL SPECIFICATIONS

<b>Scanner type</b>	ADF (Automatic Document Feeder)
<b>Scanning modes</b>	Simplex / Duplex Colour / Greyscale / Monochrome
<b>Image sensor type</b>	Dual colour CCDs (Charged Coupled Device)
<b>Light source</b>	White fluorescent lamp
<b>Scanning range</b>	<i>Minimum</i> 2.0" x 3.0" (52 x 74 mm) <i>Maximum</i> 8.5" x 34" (216 x 863 mm) / Up to 120" in long document mode <sup>10</sup>
<b>Paper weight (Thickness)</b>	11 to 56 lb. (business cards: 34 to 56 lb.) Supports ISO7810 embossed card (both portrait and landscape feedability <sup>1</sup> ; 1.4 mm thickness or less <sup>2</sup> )
<b>Scanning speed<sup>3</sup> (Letter, Portrait, 200 dpi)</b>	25 ppm / 50 ipm (colour <sup>4</sup> ) 30 ppm / 60 ipm (greyscale <sup>4</sup> or monochrome)
<b>Paper chute capacity<sup>5</sup></b>	Max. 50 sheets (letter, 20 lb.)
<b>Background</b>	Black and white (auto-switching)
<b>Optical resolution</b>	600 dpi
<b>Output resolution<sup>6</sup></b>	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi <sup>7</sup>
<b>Output format</b>	24 bit (colour), 8 bit (greyscale), or 1 bit (monochrome)
<b>AD converter</b>	10 bit
<b>Drivers</b>	TWAIN and ISIS™
<b>Interface</b>	USB2.0
<b>Connector shape</b>	B Type
<b>Output mode (Half-tone)</b>	Dither / Error diffusion
<b>Voltage</b>	AC 100 to 240 V +/-10%, 50/60 Hz
<b>Power</b>	<i>Operating</i> 38 watts or less <i>Sleep mode</i> Less than 6.2 watts
<b>Operational environment</b>	<i>Temperature</i> 5°C to 35°C (42°F to 95°F) <i>Relative humidity</i> 20% to 80% (non-condensing)
<b>Dimensions<sup>8</sup> (W x D x H)</b>	301 x 160 x 158 mm (11.8" x 6.4" x 6.2")
<b>Weight</b>	4.2 kg (9.24 lb.)
<b>Environmental compatibility<sup>9</sup></b>	EnergyStar® and RoHS
<b>Other</b>	<i>Multi-feed detection</i> Standard; Ultrasonic multi-feed detection sensor. <i>TWAIN functions</i> Auto crop, auto de-skew, auto colour detection, blank page detection, punch hole removal. <i>Dropout colour</i> Selectable dropout colour (red, green, blue, or none).

## OPTIONS

<b>fi-614PR imprinter unit</b> PA03540-D201	Assists document management by printing numbers, letters and codes on original document after they have been scanned.
--	---

## CONSUMABLES

<b>ScanAid kit</b> CG01000-524801	Up to 200,000 sheets or 1 year. The kit includes 1 pick roller, 1 brake roller, and 1 cleaning kit.
--------------------------------------	--

## SERVICE OPTIONS

<b>Post warranty maintenance coverage</b>	Provides post warranty remedial maintenance.
---	--

## BUNDLED ITEMS

	AC power cable, USB cable, Installation guide, ScandAll Pro, ISIS/TWAIN drivers
--	---

## WARRANTY

	1 year exchange warranty. Visit <a href="http://www.fujitsu.ca/warranty/scanner/">www.fujitsu.ca/warranty/scanner/</a> for more details.
--	---

1) Capable of scanning up to 3 cards at a time (Note: does not support multi-embossed card feedability).

2) Able to digitize cards that are up to 1.25 mm thick when scanning in monochrome at 200 dpi (30 ppm).

3) Actual scanning speeds are affected by data transmission and software processing times.

4) JPEG compressed figures.

5) Maximum capacity varies, depending upon paper weight.

6) Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.

7) Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600 dpi or higher).

8) Excluding the ADF paper chute and stacker.

9) PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC).

10) Scanning documents that exceed 863 mm (34 inches) in length will be limited to using TWAIN at 200 dpi or less.

Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe, Acrobat, Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Kofax, VirtualReScan, Adrenaline and the "VRS VirtualReScan" logo are registered trademarks of Kofax Image Products. All the other trademarks mentioned herein are the property of their respective owners. Specifications are subject to change without notice.  
© 2010 Fujitsu Canada, Inc. All rights reserved. FCI-02.21.2010-E

